

# SUSPENSION PSI TO LOAD CHART

**23K  
SUSPENSION  
HT230T**

USING ONE OF THESE  
HENDRICKSON  
AIR SPRINGS

**AIR SPRING  
C-20010  
C-21208**

**Required**

**Load per axle**

**psi**

**(lbs)**

**(kg)**

**98**

**23,000**

**10,433**

**89**

**21,000**

**9,525**

**80**

**19,000**

**8,618**

**71**

**17,000**

**7,711**

**62**

**15,000**

**6,804**

**53**

**13,000**

**5,897**

**44**

**11,000**

**4,990**

**35**

**9,000**

**4,082**

**26**

**7,000**

**3,175**

**18**

**5,000**

**2,268**

**10**

**3,000**

**1,361**

**Trailer Commercial Vehicle Systems**  
2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045  
FAX 800.696.4416



**HENDRICKSON**

[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

**Hendrickson Canada**  
250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
905.789.1030  
FAX 905.789.1033