HINTRAAX[®] AAL 23K / 25K / 30K Integrated Suspension Systems

- Trusted name
- Superior axle design
- Application versatility



Trusted Name

Worldwide OEMs, fleets and owner operators put their trust in INTRAAX[®]. With a well-deserved reputation for low maintenance and durability, AAL models deliver the proven benefits of INTRAAX technology to trailer designs for low-ride height or liftable suspensions.



Hendrickson's INTRAAX AAL product line now features the 5¾-inch LDA[™] Large-Diameter Axle. The road-proven LDA axle reduces weight, improves performance, increases axle stiffness and improves durability.

Application Versatility

The sleek, low-profile design of AAL models cover a wide range of ride heights from low-deck trailers to highclearance off-highway operations. The exceptional axle travel of this system also makes the AAL an ideal liftable suspension. Teamed with our UBL[™] UNDER BEAM LIFT[™], this lift axle combo provides excellent ground clearance when raised.



To learn more about INTRAAX AAL, call 866.743.3247 or visit www.hendrickson-intl.com



INTRAAX[®] AAL Features and Benefits

TRI-FUNCTIONAL® Bushing

 Rigid trailing arm and solid axle connection for optimum ride softness and stability

Standard Trailer Cam Tube System™

- Enhances S-cam alignment and helps extend life of brake components
- Short 10-inch S-cam reduces windup and bushing wear for responsive, consistent stopping power

Brake Component Mounting

 Welded to trailing arms rather than axle; minimizes axle stress

Value-Added Options

- RTR[®] READY-TO-ROLL[®] wheel-end options reduce weight, enhance durability and lower maintenance
 - HXL3[®] Hendrickson Extended-Life 3-year System[™] features a three-year limited on-highway warranty*
 - HXL5[®] Hendrickson Extended-Life 5-year System[™] features a five-year limited on-highway warranty^{*}
 - HXL7[®] Hendrickson Extended-Life 7-year System[™] features a seven-year limited on-highway warranty*

See RTR READY-TO-ROLL Wheel-End flyer - Literature No. L1200



- TIREMAAX[®] tire inflation system helps maximize tire life and maintain peak fuel mileage
- HXS[®] Hendrickson Extended Service[™] brakes extend intervals between brake service
- UBL[™] UNDER BEAM LIFT[™] is a lightweight mechanism which offers cost savings and operational flexibility
- Rear shock options available

Air disc brakes available (requires rear shock option) See Raised-Center Axle Flyer - Literature No. L1065 See TIREMAAX PRO Brochure - Literature No. L1199 See UBL UNDER BEAM LIFT Flyer - Literature No. L727

*Contact your local Hendrickson representative for complete warranty terms, conditions and limitations.

Specifications

MODEL	MAXIMUM CAPACITY (lbs.)	AXLE RATING' (lbs.)	AXLE DIAMETER	RIDE HEIGHTS (Inches)	APPLICATION WEIGHT (lbs.)
AAL 23K	23,000	23,000	LDA™	6.5, 7.5, 8, 9, 12, 14, 15, 16, 17, 19	570
AAL 25K	25,000	25,000	LDA	6.5, 7.5, 8, 9, 12, 14, 15, 16, 17, 19	586
AAL 30K	30,000	25,000	LDA	9, 12, 14, 15, 16, 17, 19	612

¹Axle structure rating only. Brakes rated separately.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.

H HENDRICKSO

TRAILER COMMERCIAL VEHICLE SYSTEMS 2070 Industrial Place SE Canton, OH 44707-2641 USA 866.RIDEAIR (743.3247) 30.489.0045 • Fax 800.696.4416 Hendrickson Canada 250 Chrysler Drive, Unit #3 Brampton, ON Canada L6S 6B6 800.668.5360 905.789.1030 • Fax 905.789.1033

Hendrickson Mexicana

Circuito El Marqués Sur #29 Parque Industrial El Marqués Pob. El Colorado, Municipio El Marqués, Querétaro, México C.P. 76246 +52 (442) 296.3600 • Fax +52 (442) 296.3601

www.hendrickson-intl.com

L1066 Rev F 02-20

© 2008 – 2020 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.