

HENDRICKSON USE ONLY

ORDERING GUIDE

HT™ SERIES 25K/30K UNDERSLUNG and Y-BEAM SUSPENSIONS

LIT NO: L555

DATE: August 2019

REVISION: J

FORM INSTRUCTIONS

For complete price and model number information on an HT250US, HT300US or HT300YB suspension, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO:	FROM:	COMPANY NAME:	
DATE:	PHONE:	FAX:	EMAIL:

SAME AS:	EXCEPT:
-----------------	----------------

SUSPENSION

SUSPENSION MODEL (capacity):	<input type="checkbox"/> HT250US (25K)	<input type="checkbox"/> HT300US (30K)				
AXLE CONNECTION:	None					
RIDE HEIGHT (inches):	<input type="checkbox"/> 3.5" (25K only) <input type="checkbox"/> 12"	<input type="checkbox"/> 4" (25K only) <input type="checkbox"/> 14"	<input type="checkbox"/> 5.5" <input type="checkbox"/> 17" (30K only)	<input type="checkbox"/> 6.5"	<input type="checkbox"/> 7.5"	<input type="checkbox"/> 9"
TRAVEL:	<input type="checkbox"/> Standard	<input type="checkbox"/> Limited Jounce	<input type="checkbox"/> Extended Rebound			
FRAME ATTACHMENT:	<input type="checkbox"/> Weld-On	<input type="checkbox"/> Bolt-On	<input type="checkbox"/> Other			
AIR SPRING PSI RANGE:	<input type="checkbox"/> Standard	<input type="checkbox"/> High Pressure (25K only)				
AIR SPRING MOUNTING PLATE:	<input type="checkbox"/> Standard	<input type="checkbox"/> Rotated (25K only)	<input type="checkbox"/> None			
SHOCK ABSORBER:	<input type="checkbox"/> Standard	<input type="checkbox"/> Extended Service / High Damping ¹				
SHOCK MOUNTING:	<input type="checkbox"/> Forward Upper Mount (Standard)	<input type="checkbox"/> Remote Mount				
SHOCK STRAPS:	<input type="checkbox"/> Yes	<input type="checkbox"/> No				
FRAME BRACKET TO BEAM:	<input type="checkbox"/> Assembled	<input type="checkbox"/> Non-Assembled				
TIRE SIZE (inches): (To determine U-bolt)	<input type="checkbox"/> 17.5" (25K only)	<input type="checkbox"/> 19.5" or larger				
FRAME BRACKET SUPPORT (C-Channel):	<input type="checkbox"/> Weld-on C-Channel	<input type="checkbox"/> Customer Supplied				
HIGH CONTROL SUSPENSION²:	<input type="checkbox"/> Yes	<input type="checkbox"/> No				
AXLE STYLE:	<input type="checkbox"/> Standard	<input type="checkbox"/> Steerable (25K only)				
BRAKE TYPE:	Drum Only (Air disc brakes not available)					
BEAM COATING (Suspension Coating):	<input type="checkbox"/> Standard Black Primer	<input type="checkbox"/> None				
FRAME COMPONENTS COATING: (Frame Bracket Coating)	<input type="checkbox"/> Standard Black Primer	<input type="checkbox"/> None / Do not paint frame brackets				



Are you ordering a Y-Beam suspension? No Yes (continue to page 2)

1. Required for HT300US suspension.
2. High control suspensions are recommended for single-axle trailers in multi-trailer combinations, all dollies and full trailers with two single axles. Not for use on multiple-axle trailers.

NOTE: Some combinations may not be compatible or available.

HENDRICKSON

SUSPENSION

SUSPENSION MODEL (capacity):	<input type="checkbox"/> HT300YB ³ (30K Y-Beam)
AXLE CONNECTION:	None
RIDE HEIGHT (inches):	<input type="checkbox"/> 6.5" <input type="checkbox"/> 7.5" <input type="checkbox"/> 9"
TRAVEL:	Standard
FRAME ATTACHMENT:	Y-Beam
AIR SPRING PSI RANGE:	Standard
AIR SPRING MOUNTING PLATE:	<input type="checkbox"/> Standard <input type="checkbox"/> None
SHOCK ABSORBER:	Standard
SHOCK MOUNTING:	Forward Upper Mount (Standard)
SHOCK STRAPS:	<input type="checkbox"/> Yes <input type="checkbox"/> No
FRAME BRACKET TO BEAM:	Non-Assembled
TIRE SIZE (inches):	19.5" or larger
FRAME BRACKET SUPPORT (C-Channel):	None (Y-Beam)
HIGH CONTROL SUSPENSION:	No
AXLE STYLE:	Standard
BRAKE TYPE:	Drum Only (Air disc brakes are not available)
BEAM COATING (Suspension Coating):	<input type="checkbox"/> Standard Black Primer <input type="checkbox"/> None
FRAME COMPONENTS COATING: (Frame Bracket Coating)	None

3. For use in conjunction with HT300US suspensions.

*Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.
All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.
Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.*

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

L964 Rev J 08-19

© 2007 - 2019 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries. Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada

250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
800.668.5360
905.789.1030 • Fax 905.789.1033

Hendrickson Mexicana

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601