HINTRAAX[®] AANLS 20K Integrated Suspension System

- Trusted name
- Superior axle design
- Compact design for autohaulers, moving vans and drop-frames



Trusted name

Worldwide OEMs, fleets and owner operators put their trust in INTRAAX® integrated suspension systems. With a reputation for low maintenance and durability, the INTRAAX suspension helps offer a smooth ride, exceptional performance and the durability needed to protect cargo and keep equipment operating at peak performance. Known for its light weight, the INTRAAX AANLS model trims an average of 120 pounds per axle compared to similar suspensions.

Superior axle design

The AANLS model uses a narrow, tapered-beam design for reduced weight compared to a straight beam. The narrow pivot, taperedbeam configuration uses the high performance TRI-FUNCTIONAL® III Bushing, which delivers the same smooth ride and enhanced bushing life as our wide diameter bushing model.

Compact design for autohaulers, moving vans and drop-frames

Weighing in at 542 pounds for a standard configuration, the AANLS 20K model is the optimum system for autohaulers, moving vans and drop-frame trailers. Available in ride heights from 6.25 to 12 inches, this 20,000-pound capacity system features shortened trailing arms to provide a compact profile ideally suited to the tight confines of autohaulers and drop-frame trailer designs.

To learn more about INTRAAX AANLS, call 866.743.3247 or visit www.hendrickson-intl.com



INTRAAX® AANLS 20K System Features and Benefits



- Value-Added Options
- RTR[®] READY-TO-ROLL[®] wheel-end options reduce weight, enhance durability and lower maintenance
 - HXL3[®] Hendrickson Extended-Life 3-year System[™] features a three-year limited on-highway warranty*
 - HXL5[®] Hendrickson Extended-Life 5-year System[™] features a five-year limited on-highway warranty*

See RTR READY-TO-ROLL Wheel-End flyer - L1200

*Contact your local Hendrickson representative for complete warranty terms, conditions and limitations.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

- TIREMAAX[®] tire inflation system helps maximize tire life and maintain peak fuel mileage
- Forward-mounted standard or extended service high damping shock absorbers available to optimize ride control for your specific operation
- Both 15 and 16.5 inch brake options for compatibility with a variety of tire sizes
- Available with air disc brakes including Hendrickson's MAXX22T[™] optimized trailer air disc brakes

See TIREMAAX PRO Brochure - L1199 See MAXX22T Flyer - L1239

Specifications

MODEL	SUSPENSION	AXLE	RIDE	BASE MODEL
	CAPACITY	DIAMETER	HEIGHTS	WEIGHT
	(lbs.)	(Inches)	(Inches)	(lbs.)
AANLS	20,000*	5	6.25, 7, 9, 12	542

*Capacity refers to suspension and axle ratings, except where noted.

Ratings for brakes and wheel-end components differ depending upon options chosen.

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



 TRAILER COMMERCIAL VEHICLE SYSTEMS

 2070 Industrial Place SE

 Canton, OH 44707-2641 USA

 866.RIDEAIR (743.3247)

 330.489.0045 • Fax 800.696.4416

Hendrickson Canada 250 Chrysler Drive, Unit #3 Brampton, ON Canada L6S 6B6 800.668.5360 905.789.1030 • Fax 905.789.1033

Hendrickson Mexicana

Circuito El Marqués Sur #29 Parque Industrial El Marqués Pob. El Colorado, Municipio El Marqués, Querétaro, México C.P. 76246 +52 (442) 296.3600 • Fax +52 (442) 296.3601

www.hendrickson-intl.com

L817 Rev H 01-18