

HENDRICKSON USE ONLY

ORDERING GUIDE

CONNEX[®] SUSPENSION

LIT NO: L1274

DATE: December 2020

REVISION: D

FORM INSTRUCTIONS

For complete price and model number information on a CONNEX[®] suspension system, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO:		FROM:		COMPANY NAME:	
DATE:	PHONE:	FAX:	EMAIL:		

SAME AS:	EXCEPT:
-----------------	----------------

SUSPENSION	
SUSPENSION MODEL:	<input type="checkbox"/> CXU 23K <input type="checkbox"/> CXU 25K <input type="checkbox"/> CXY 23k (Y-Beam) <input type="checkbox"/> CXY 25k (Y-Beam)
RIDE HEIGHT (inches):	<input type="checkbox"/> 5.5 <input type="checkbox"/> 6.5 <input type="checkbox"/> 7.5 <input type="checkbox"/> 9.0
FRAME BRACKET:	<input type="checkbox"/> Weld-on <input type="checkbox"/> Bolt-on <input type="checkbox"/> HTZUS (Slider)
FRAME BRACKET MOUNTING:	<input type="checkbox"/> Standard Weld-on <input type="checkbox"/> Universal Pattern, 5/8" Bolt Dia.
FRAME BRACKET STYLE:	<input type="checkbox"/> Wingless <input type="checkbox"/> Y-Beam
SHOCK ABSORBER:	<input type="checkbox"/> Standard <input type="checkbox"/> Extended Service / High Damping
SHOCK STRAPS:	<input type="checkbox"/> No <input type="checkbox"/> Yes
TRAVEL:	<input type="checkbox"/> Standard <input type="checkbox"/> Limited Jounce
AIR SPRING PSI RANGE:	Standard
AIR SPRING MOUNTING STUD:	<input type="checkbox"/> Dual Combo Stud, Standard <input type="checkbox"/> Single Combo Stud, Rotated
FRAME BRACKET SUPPORT:	<input type="checkbox"/> Weld-on Channel <input type="checkbox"/> Bolt-on with strut ¹ <input type="checkbox"/> Customer Supplied <input type="checkbox"/> N/A
BUSHING TUBE SPACER:	Standard (flat)
FRAME BRACKET TO BEAM:	<input type="checkbox"/> Assembled <input type="checkbox"/> Separate Frame Kit <input type="checkbox"/> HTZUS
BEAM / AXLE COATING:	<input type="checkbox"/> Standard Black Primer <input type="checkbox"/> Finish Soft Coat - Black
COMPONENT COATING / COVER: (Frame Brackets and Air Spring Mounts)	<input type="checkbox"/> Standard Black Primer <input type="checkbox"/> Galvanized ² <input type="checkbox"/> None

1. Only available with bolt-on frame brackets. Coating will match selected coating on frame brackets.

2. Only available with CXY and HTZUS options.

AXLE					
STYLE:	Straight				
TRACK (inches):	<input type="checkbox"/> 71.5"	<input type="checkbox"/> 77.5"	<input type="checkbox"/> 77.5"	<input type="checkbox"/> 77.5"	<input type="checkbox"/> 77.5"
Suspension Beam Centers (by track):	35.0"	37.0"	38.25"	39.0"	41.0"
S-CAM ORIENTATION:	<input type="checkbox"/> Cams Rear (Standard) <input type="checkbox"/> Cams Forward (Required for some lift kits. Contact Hendrickson.)				
SPINDLE:	<input type="checkbox"/> HP <input type="checkbox"/> HN				
TIRE INFLATION SYSTEM:	<input type="checkbox"/> TIREMAAX® CP (complete worksheet on pg.4) <input type="checkbox"/> TIREMAAX PRO (complete worksheet on pg.4) <input type="checkbox"/> No				

DRUM BRAKES *		*Slack and brake chamber combinations will affect brake ratings. Refer to L809 Brake Certifications.					
BRAKE LINING:	<input type="checkbox"/> H20 <input type="checkbox"/> H23 <input type="checkbox"/> H26						
BRAKE SIZE:	<input type="checkbox"/> 12.25" x 7.5" <input type="checkbox"/> 16.5" x 7.0" <input type="checkbox"/> 16.5" x 8.63"						
BRAKE MODEL:	HXS®						
BRAKE COATING:	<input type="checkbox"/> Standard <input type="checkbox"/> AAXTREME Coat						
BRAKE CHAMBERS³:	<input type="checkbox"/> None	<input type="checkbox"/> 2.5" Standard Stroke				<input type="checkbox"/> 3.0" Long Stroke	
SIZE / WARRANTY:		<input type="checkbox"/> Type 30/30 Standard Warranty	<input type="checkbox"/> Type 30/30 Extended Warranty	<input type="checkbox"/> Type 24/30 Standard Warranty	<input type="checkbox"/> Type 24/24 Standard Warranty	<input type="checkbox"/> Type 30/30 Standard	<input type="checkbox"/> Type 30/30 Extended Warranty
SLACK ADJUSTER:	<input type="checkbox"/> None	<input type="checkbox"/> Standard 5.5"			<input type="checkbox"/> Standard 6.0"		
S-CAM:	28 Spline						
DUST SHIELD:	<input type="checkbox"/> No <input type="checkbox"/> Yes						
ABS SENSOR:	<input type="checkbox"/> No	<input type="checkbox"/> Haldex 19.7"	<input type="checkbox"/> WABCO 15.7"	<input type="checkbox"/> WABCO 36"	<input type="checkbox"/> Bendix 14.84"	<input type="checkbox"/> Bendix 78.7"	

3. Unless otherwise indicated, standard brand will be provided.

DRUM BRAKE RTR® READY-TO-ROLL® PACKAGES		
	<input type="checkbox"/> HXL3® Hendrickson Extended-Life System™ (3-Year Limited Warranty ⁴)	<input type="checkbox"/> HXL5® Hendrickson Extended-Life System™ (5-Year Limited Warranty ⁴)
SPINDLE:	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP
HUB MATERIAL:	<input type="checkbox"/> Ductile Iron <input type="checkbox"/> ADI <input type="checkbox"/> Aluminum	<input type="checkbox"/> Ductile Iron <input type="checkbox"/> ADI <input type="checkbox"/> Aluminum
HUB STYLE:	Hub Piloted	Hub Piloted
NUMBER OF STUDS (Bolt Circle Diameter):	<input type="checkbox"/> 8 (275mm) <input type="checkbox"/> 10 (11.25")	<input type="checkbox"/> 8 (275mm) <input type="checkbox"/> 10 (11.25")
WHEEL MATERIAL:	<input type="checkbox"/> Aluminum <input type="checkbox"/> Steel <input type="checkbox"/> Steel / Aluminum	<input type="checkbox"/> Aluminum <input type="checkbox"/> Steel <input type="checkbox"/> Steel / Aluminum
DUAL / SUPER SINGLE: (SS) Short Stud (LS) Long Stud	<input type="checkbox"/> Dual <input type="checkbox"/> Super Single (SS) <input type="checkbox"/> Super Single (LS)	<input type="checkbox"/> Dual <input type="checkbox"/> Super Single (SS) <input type="checkbox"/> Super Single (LS)
LUBE TYPE:	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90	Semi-Fluid Grease
SEAL:	Standard	Standard
BEARING:	Standard	Standard
SPINDLE NUT:	PRECISION240® Nut System or PRECISION320® Nut System	PRECISION240® Nut System or PRECISION320® Nut System
HUBCAP TYPE:	Standard Aluminum Bolt-On	Standard Aluminum Bolt-On
ABSTONE RING:	Yes	Yes

DRUM OPTIONS	
DRUM MATERIAL:	<input type="checkbox"/> Cast <input type="checkbox"/> Fused
DRUM DUTY:	<input type="checkbox"/> Standard <input type="checkbox"/> Heavy Duty <input type="checkbox"/> Special Duty (16.5" × 8.63" Brakes only)
DRUM BALANCING:	Balanced
WHEEL FASTENERS⁵:	<input type="checkbox"/> Yes <input type="checkbox"/> No

ACCESSORY ITEMS		Not included in CONNEX model number - Sold Separately.	
HEIGHT CONTROL VALVE:	<input type="checkbox"/> Yes <input type="checkbox"/> No	Integral Dump:	<input type="checkbox"/> Yes <input type="checkbox"/> No
MANUAL DUMP VALVE:	<input type="checkbox"/> Yes <input type="checkbox"/> No	With Enclosure:	<input type="checkbox"/> Yes <input type="checkbox"/> No
UNIVERSAL LOAD SCALE KIT:	<input type="checkbox"/> Yes <input type="checkbox"/> No		
LIFT KIT⁶:	<input type="checkbox"/> Yes <input type="checkbox"/> No		
HTZUS SLIDER BOX:	<input type="checkbox"/> Yes <input type="checkbox"/> No		

4. Refer to Hendrickson publication "L583 - Comprehensive Warranty Statement" for complete details.

5. Two (2) wheel fasteners factory installed per wheel-end with balance packaged in parts box.

6. Contact Hendrickson to verify lift kit part numbers and compatibility.

TIREMAAX® KIT WORKSHEET^{7, 8}

Not included in CONNEX model number - Sold Separately.

CONTROLLER TYPE:	<input type="checkbox"/> CP	<input type="checkbox"/> PRO									
ELECTRICAL CONNECTION:	<input type="checkbox"/> Delphi Weather Pack (Standard)	<input type="checkbox"/> Blade Terminals ⁹									
NUMBER OF AXLES:	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> Other						
HUBCAP TYPE:	Hendrickson Bolt-On										
LUBE TYPE:	<input type="checkbox"/> Semi-Fluid Grease	<input type="checkbox"/> Oil									
WHEEL STYLE / MATERIAL:	<input type="checkbox"/> Dual / Aluminum	<input type="checkbox"/> Dual / Steel or Combo	<input type="checkbox"/> Super Single / Aluminum (straight hose)								
	<input type="checkbox"/> Super Single / Steel (inboard valve stem; straight hose)		<input type="checkbox"/> Super Single / Steel (outboard valve stem; 180-degree hose)								
TIRE SIZE:	<input type="checkbox"/> 17.5"	<input type="checkbox"/> 19.5"	<input type="checkbox"/> 22.5"	<input type="checkbox"/> 24.5"							
COLD TIRE PRESSURE SETTING (psi)¹⁰:	<input type="checkbox"/> 70	<input type="checkbox"/> 75	<input type="checkbox"/> 80	<input type="checkbox"/> 85	<input type="checkbox"/> 90	<input type="checkbox"/> 95	<input type="checkbox"/> 100	<input type="checkbox"/> 105	<input type="checkbox"/> 110	<input type="checkbox"/> 115	<input type="checkbox"/> 120
TIRE HOSE:	<input type="checkbox"/> Standard	<input type="checkbox"/> Integral Check Port (22.5" tire size only)									
TRAILER-MOUNTED INDICATOR LIGHT KIT:	<input type="checkbox"/> LED - 12V with 65-foot Cable (Standard)	<input type="checkbox"/> LED - 12V with 35-foot Cable	<input type="checkbox"/> LED - 24V (Export ¹¹)								
	<input type="checkbox"/> Incandescent - 12V	<input type="checkbox"/> No ⁹									
WIRING HARNESS:	<input type="checkbox"/> Premium, 15-foot, ABS-ready	<input type="checkbox"/> Premium, 3-foot, ABS-ready	<input type="checkbox"/> Standard, 18-inch, Wring Adapter Plug	<input type="checkbox"/> No ⁹							
AIR PLUMBING KIT:	<input type="checkbox"/> Manifold ¹²	<input type="checkbox"/> No									
CONTROLLER TANK VALVE¹³: (Pressure Check)	<input type="checkbox"/> Yes (CP Models Only)	<input type="checkbox"/> No									

7. Hendrickson does not provide warranty coverage for the installation, performance or components of a competitor brand tire inflation system installed on a Hendrickson suspension or trailer axle. Any consequential damages to the Hendrickson suspension or trailer axle resulting from a failure to the competitor brand tire inflation system or components, whether installed by the OEM, repair facility or end-user customer, should be directed to the respective tire inflation system manufacturer for warranty coverage.

8. When installing TIREMAAX, please contact Hendrickson to verify correct wheel-end component integration.

9. Controllers featuring blade terminals require the light kit and wiring harness options to be "no".

10. Refer to tire manufacturer's recommended tire pressure. TIREMAAX PRO is restricted to cold tire pressure setting of 85-120 psi.

11. Please note, 12V is used in some export countries. If this is a new venture into a foreign country, please validate voltage requirements with Controls Engineering.

12. Not available for single-axle systems.

13. Not available with TIREMAAX PRO.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.

Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

L1274 Rev D 12-20

© 2016 - 2020 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries.

Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada

250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
800.668.5360
905.789.1030 • Fax 905.789.1033

Hendrickson Mexicana

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601