

- Superior weight savings
- Assistance with applicable bridge and weight law compliance
- Flexibility to haul across borders



#### **Weight Savings and Exceptional Durability**

VANTRAAX<sup>®</sup> tridem sliders incorporate the road-proven INTRAAX<sup>®</sup> integrated suspension system and patented<sup>▲</sup> K-2<sup>®</sup> slider box for exceptional durability with superior weight savings. The K-2 slider box design provides an outstanding strength to weight ratio allowing operators to load more cargo per haul. The patented "K" bracing reduces weight while increasing durability and its simple design opens interior spacing for easier plumbing and maintenance.

<sup>▲</sup> This product is covered by at least one or more U.S. and/or foreign patents and/or pending U.S. and/or foreign patent applications. See Hendrickson for details.

#### **Hauling Flexibility Across Borders**

Tridem sliders gives operators the flexibility to haul across international, provincial and state borders while helping them comply with a wide variety of bridge and weight laws and Canadian "infrastructure-friendly" regulations. With an overall system rating of 69,000 pounds, the tridem is available with a 23,000-pound standard duty suspension with a narrow pivot connection (HKANT 69K23) or a 25,000-pound heavy duty suspension (69K25).

To learn more about VANTRAAX,  
call 866.743.3247 or visit  
[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

**H** **HENDRICKSON**  
*The World Rides On Us*<sup>®</sup>

# VANTRAAX® Features and Benefits

## TRI-FUNCTIONAL® Bushing

- Controls vertical, horizontal and roll forces of trailer
- Optimizes ride softness, control and stability

## Neutral-Toe Axle

- Helps increase fuel economy and tire life
- Straight tracking

## Axle Wrap and Window Weld

- Provides optimal structural integrity

## QUIK-ALIGN® Pivot Connection

- Fast and easy axle alignment
- Requires no welding or special tools

## QUIK-DRAW® Fully Pneumatic Pin-Pull Mechanism

- Automatic reset engages pins when parking brake releases
- Driver Friendly – finger-tip operation
- Helps reduce driver strain and enhances productivity



## Diagonal "K" Bracing

- K-brace prevents racking, increases strength and slider life

## Advanced Trailer Cam Tube System™

- Enhances S-cam alignment and helps extend life of brake components
- Short 10-inch S-cam reduces windup and bushing wear for responsive, consistent stopping power

## Value-Added Options

- RTR® READY-TO-ROLL® wheel-end options reduce weight, enhance durability and lower maintenance
  - HXL3™ Hendrickson Extended-Life 3-year System™ features a three-year limited on-highway warranty\*
  - HXL5™ Hendrickson Extended-Life 5-year System™ features a five-year limited on-highway warranty\*
  - HXL7™ Hendrickson Extended-Life 7-year System™ features a seven-year limited on-highway warranty\*
- TIREMAAX® tire inflation system helps maximize tire life and maintain peak fuel mileage
- HXS® Hendrickson Extended Service™ brakes extend intervals between brake service
- SURELOK® limits vertical and horizontal movement during loading and unloading

See TIREMAAX PRO Brochure - Literature No. L1199

See SURELOK Flyer - Literature No. L622

See RTR READY-TO-ROLL Wheel-End flyer - Literature No. L1200

\*Contact your local Hendrickson representative for complete warranty terms, conditions and limitations.

## Specifications

MODEL	Axle Spacing (inches)	System Capacity (pounds)	Axle Rating (pounds)	Axle Diameter (Inches)	Box Width (Inches)	Ride Heights (Inches)	Base Model Weight (pounds)
HKANT 69K23	49, 60, 72	69,000	23,000	5.75	48, 54	16, 16.5, 17, 18	2,236
HKAT 69K25	60, 72	69,000	25,000	5.75	42, 48, 54	16, 17, 18	2,479

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

### TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045 • Fax 800.696.4416

### Hendrickson Canada

250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
800.668.5360  
905.789.1030 • Fax 905.789.1033

### Hendrickson Mexicana

Circuito El Marqués Sur #29  
Parque Industrial El Marqués  
Pob. El Colorado, Municipio El Marqués,  
Querétaro, México C.P. 76246  
+52 (442) 296.3600 • Fax +52 (442) 296.3601

L875 Rev E 06-19

© 2004 – 2019 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries. Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

Printed in United States of America