HINTRAAX[®] RCA Raised-Center Axle System

- Boost trailer productivity
- Increase value
- Optimized design for rear-discharge tankers





To learn more about INTRAAX RCA, call 866.743.3247 or visit www.hendrickson-intl.com



INTRAAX[®] RCA System Features and Benefits



- RTR[®] READY-TO-ROLL[®] wheel-end options reduce weight, enhance durability and lower maintenance
 - HXL3[®] Hendrickson Extended-Life 3-year System[™] features a three-year limited on-highway warranty*
 - HXL5[®] Hendrickson Extended-Life 5-year System[™] features a five-year limited on-highway warranty*
 - HXL7[®] Hendrickson Extended-Life 7-year System[™] features a seven-year limited on-highway warranty*
- HXS[®] Hendrickson Extended Service[™] brakes extend intervals between brake service

See RTR READY-TO-ROLL Wheel-End flyer - L1200

*Contact your local Hendrickson representative for complete warranty terms, conditions and limitations.

- Air disc brakes available including Hendrickson MAXX22T[™] optimized trailer air disc brake
- TIREMAAX[®] tire inflation system helps maximize tire life and maintain peak fuel mileage
- Cap-style bushing tube spacers are recommended in tanker applications
- ZMD[®] ZERO MAINTENANCE DAMPING[®] shockless ride technology available on select AAT 23K / 25K RCA models

See TIREMAAX PRO Brochure - L1199 See MAXX22T flyer - L1239 See ZMD flyer - L1209

Specifications

MODEL	SUSPENSION CAPACITY (pounds)	AXLE DIAMETER (inches)	AXLE TRACKS (inches)	RIDE HEIGHTS (inches)	BASE MODEL WEIGHT (pounds)
AAT 23K ¹	23,000	5	71.5 and 77.5	13.5, 14, 15, 16, 17, 18, 19	597
AAT 25K ¹	25,000 ²				
AAL 23K	23,000	5	77.5	8, 9, 12,14, 15, 16, 17, 19	649
AAL 25K	25,000 ²				

1. ZMD is available on select AAT 23K / 25K RCA models. RCA is recommended with limited rebound travel. ZMD is available on models with limited rebound travel and 14" or 16" ride heights only. Additionally, ZMD is available on models with standard travel and 14" - 17" ride heights.

2. Axle rated only for 23,000 pounds. Brakes rated separately.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at 330.489.0045 or 866.RIDEAIR (743.3247) for additional information.

Hendrickson

TRAILER COMMERCIAL VEHICLE SYSTEMS 2070 Industrial Place SE Canton, OH 44707-2641 USA 866.RIDEAIR (743.3247) 30.489.0045 • Fax 800.696.4416 Hendrickson Canada 250 Chrysler Drive, Unit #3 Brampton, ON Canada L6S 6B6 800.668.5360 905.789.1030 • Fax 905.789.1033 Hendrickson Mexicana

Circuito El Marqués Sur #29 Parque Industrial El Marqués Pob. El Colorado, Municipio El Marqués, Querétaro, México C.P. 76246 +52 (442) 296.3600 • Fax +52 (442) 296.3601

www.hendrickson-intl.com

L1065 Rev I 06-20

© 2008 - 2020 Hendrickson USA, LL.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, LL.C., or one of its affiliates, in one or more countries, except for MAXX22T, which is owned by WABCO Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.