




# PRIMAAX<sup>®</sup> EX

Severe-Duty Truck  
Vocational Air Suspension



A PACCAR COMPANY

- MAAximize durability
- MAAximize driver comfort
- MAAximize performance



PRIMAAX<sup>®</sup> EX is a severe-duty vocational air suspension designed specifically for the rigorous demands of vocational, severe service and heavy haul applications. The system provides technologically advanced features designed to enhance durability, reliability and handling characteristics.



To learn more about PRIMAAX EX,  
call 855.743.3733 or visit  
[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

 **HENDRICKSON**

*The World Rides On Us<sup>®</sup>*

# PRIMAAX® EX Features and Benefits

## Genuine Hendrickson Torque Rods

- Optimized configuration helps improve handling and roll stiffness for expanded applications
- Premium retained rubber bushings for increased service life and resistance to walkout
- Alternative rods available for disc brake use

## QUIK-ALIGN®

- Allows for easy axle alignment without shims
- Reduces maintenance time and helps extend tire life

## Axle Connections

- D-pin axle connection decreases torsional axle stress for reduced maintenance and improved joint integrity
- Integrated axle stop contact pads reduce axle stress

## Air Springs

- Large volume, low frequency design for improved ride
- Advanced design air springs provide fast fill time

## Structural Beams

- Integrate end caps for increased reliability
- Utilize premium materials for high durability
- Robust rubber bushings improve service life and eliminate lubrication requirements

## Height Control Valve

- Maintains proper suspension ride height
- Twin height control valves available for improved leveling in applications with uneven loading

## Heavy-Duty Shock Absorbers

- Positioned and tuned for optimum damping characteristics

## Cross Beams

- Seamless fabrication technology forms a robust torsion system with structural beams, improving stability

	PAX EX 232T	PAX EX 262T	PAX EX 262S	PAX EX 462	PAX EX 522	PAX EX 692
Axle Configuration	Single	Single	Single	Tandem	Tandem	Tridem
Site Travel Rating	30,000 lbs.	33,000 lbs.	33,000 lbs.	60,000 lbs.	66,000 lbs.	90,000 lbs.
Axle Travel	8 in.	8 in.	8 in.	8 in.	8 in.	8 in.
Ground Clearance	10.75 in.	10.75 in.	9.00 in.	10.75 in.	10.5 in.	10.75 in.
Ride Heights	15.5 in.	15.5 in.	8.5 in.	10 in.	10 in.	10 in.
Axle Spacing	N/A	N/A	N/A	52 - 72.5 in.	54 - 72.5 in.	52 - 60 in.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at **630.910.2800** or **855.RIDERED (743.3733)** for additional information.



www.hendrickson-intl.com

## TRUCK COMMERCIAL VEHICLE SYSTEMS

800 South Frontage Road  
Woodridge, IL 60517-4904 USA  
855.RIDERED (743.3733)  
630.910.2800 • Fax 630.910.2899



A PACCAR COMPANY

www.kenworth.com

45745-250 Rev G 06-20

© 2011 - 2020 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries, except for Kenworth, the Kenworth logo and PACCAR, which are owned by PACCAR Inc. Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

Printed in United States of America