TIREMAAX® TIRE INFLATION SYSTEM

This TIREMAAX[®] controller is factory preset to a cold inflation pressure of:

psi

If the indicator lamp remains on continuously for more than 10 minutes, one or more tires may be low or the system requires service. In the event of a system leak, set the trailer park brake, then close the controller supply valve.

NOTE: If equipped with TIREMAAX PRO, while trailer park brakes are set, lamp operation is disabled and no delivery pressure is present.

For complete service details, refer to Hendrickson publication T51002, TIREMAAX Installation, Service and Troubleshooting Procedures or call the Hendrickson Technical Services Department in the United States and Canada at 866-RIDEAIR (743-3247).

This article is covered by at least one or more U.S. and/or foreign patents and/or pending U.S. and/or foreign patent applications posted at www.Hendrickson-inll.com/patents.

Trailer Commercial Vehicle Systems 2070 Industrial Place SE Canton, OH 44707-2641 USA 866.RIDEAIR (743.3247) 330.489.0045 FAX 800.696.4416



Trailer Commercial Vehicle Systems 250 Chrysler Drive, Unit #3 Brampton, ON Canada L6S 6B6 905.789.1030 FAX 905.789.1033

T50015 Rev B 12-16 ECN 26079 Printed in the United States of America

©2016 Hendrickson USA, L.L.C. (U.S. Rights) Hendrickson Intl Corp. (Rights Outside U.S.) All Rights Reserved