

# **PIVOTING MUD FLAP BRACKETS**

- Helps prevent mud flap and bracket damage
- Reduces maintenance
- Exclusively on ULTRAA-K® Systems



### **Helps prevent mud flap and bracket damage**

Hendrickson's patented<sup>▲</sup> pivoting mud flap brackets are spring-loaded to allow mud flaps to rotate downward. This reduces the potential for bent mud flap mounting angles and the chances of the mud flap being pulled off or damaged.

▲ This product is covered by at least one or more U.S. and/or foreign patents and/or pending U.S. and/or foreign patent applications. See Hendrickson for details.

### **Reduces maintenance**

Traditional brackets can be damaged or broken from the force of the mud flap being pinched between the tire and a tall curb or other object. Hendrickson's patented pivoting mud flap brackets allow the entire mud flap to pivot down. This helps prevent damage, which reduces maintenance and downtime.

### **Exclusively on ULTRAA-K®**

Pivoting mud flap brackets are standard on ULTRAA-K air slider suspension systems, which also includes other low maintenance features like ZMD® ZERO MAINTENANCE DAMPING® TECHNOLOGY and pre-installed, protected height control valve to help maximize maintenance savings.

To learn more about ULTRAA-K system, call 866.743.3247 or visit [www.hendrickson-intl.com](http://www.hendrickson-intl.com)

 **HENDRICKSON**  
*The World Rides On Us®*

## PIVOTING MUD FLAP BRACKETS - How They Work



Pivoting mud flap brackets are more effective at preventing component damage than traditional brackets. If the mud flap is pinched between the tire and an obstacle behind the trailer, the entire bracket can rotate in the same direction as the flap is being pulled.



Tension is evenly distributed along the top of the mud flap as the brackets rotate downward, protecting the outermost edges of the mud flap from being torn. Since the brackets are spring-loaded, once the mud flaps are no longer pinched and pulled, the brackets return everything back into place undamaged and ready for continued operation.

### Additional Features




#### Welded on Bracket Nuts

- Simple and efficient installation

#### Angle Compatibility

- Additional mounting holes allow the bracket to be shifted inboard, aligning the outer edge with wide-base single tires



### Warranty

#### Mud Flap Bracket Assembly Warranty Comparison

MODEL	PARTS	LABOR
Pivoting Mud Flap Bracket Assembly - ULTRAA-K UTKNT 40K*	3 years	1 year
Typical Industry Mud Flap Brackets	1 year	1 year

*\*Refer to Hendrickson Lit No. L583 for complete warranty terms, conditions and limitations.*

*Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.*

*All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.*

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

#### TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045 • Fax 800.696.4416

#### Hendrickson Canada

250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
800.668.5360  
905.789.1030 • Fax 905.789.1033

#### Hendrickson Mexicana

Circuito El Marqués Sur #29  
Parque Industrial El Marqués  
Pob. El Colorado, Municipio El Marqués,  
Querétaro, México C.P. 76246  
+52 (442) 296.3600 • Fax +52 (442) 296.3601