# **HTRLAXLE**<sup>®</sup> Non-Integrated Trailer Axles

- Wide variety of suspension / axle configurations
- Versatility for the global market
- Low-maintenance



### Axle that fits global needs

Hendrickson offers a full line of industry standard, low maintenance non-integrated trailer axles to fit a variety of configurations for the global, commercial and industrial vehicle markets. TRLAXLE® trailer axles are available in numerous spindle types, capacities and axle tracks, drum or air disc brakes, 121/4- to 161/2-inch brakes and many RTR® READY-TO-ROLL® wheel-ends, slack adjuster and brake chamber options - to fit either air or mechanical spring applications.

By combining Hendrickson TRLAXLE trailer axles with HT<sup>™</sup> Series air suspensions, Hendrickson offers a wide variety of suspension / axle combinations and application coverage. TRLAXLE trailer axles deliver a low cost, low maintenance solution and superior customer and warranty support.



To learn more about TRLAXLE, call 866.743.3247 or visit www.hendrickson-intl.com



## TRLAXLE® Trailer Axle Features and Benefits

# Available in 1/2- to 3/4-inch wall Patented<sup>A</sup> axle filter protects the wheel-end from contamination Hendrickson Proprietary Brake Linings Available in standard service and HXS<sup>®</sup> Hendrickson Extended Service<sup>™</sup> brake shoes

Drum Brakes

### Standard S-Cam Lengths

Axle

 17 5/8-, 20 5/8- and 23 3/4-inches with numerous other lengths available

Axle capacities from 20,000 to 27,000 pounds

### Cam Tube (Cam Cover)

- · Cam tube option to extend cam life
- Available for limited cam lengths: 11 1/8-, 17 5/8-, 20 5/8-, 22 5/8-, 23 3/4-, 24 1/4-, 25 1/2-, 26 1/2- and 28 3/8-inches
- This product is covered by at least one or more U.S. and/or foreign patents and/ or pending U.S. and/or foreign patent applications. See Hendrickson for details.

### **TRLAXLE Trailer Axle** Value-Added Options

- RTR<sup>®</sup> READY-TO-ROLL<sup>®</sup> wheel-end options reduce weight, enhance durability and lower maintenance
  - HXL3<sup>®</sup> Hendrickson Extended-Life 3-year System<sup>™</sup>
  - HXL5<sup>®</sup> Hendrickson Extended-Life 5-year System<sup>™</sup>
  - HXL7<sup>®</sup> Hendrickson Extended-Life 7-year System™
- Ductile iron, Dura-Light Hub<sup>®</sup> or aluminum hubs
- Standard and heavy-duty drums
- TIREMAAX<sup>®</sup> tire inflation system helps maximize tire life and maintain peak fuel mileage
- Air disc brakes available, including Hendrickson's MAXX22T<sup>™</sup> optimized trailer air disc brake, with limited tracks and no 3/4-inch wall

### **HP and HN Spindles**

- Friction-welded
- Parallel spindle promotes even lubrication of inner and outer bearings
- Approved for wide base tires using 2-inch offset rims (HP spindles ONLY)

• 12 1/4-, 15-, 16 1/2-inch brake shoe diameters in various widths

- 5.5- or 6-inch slack adjusters
- Brake chambers in various configurations
- Dust shields (15- and 16 1/2-inch brake size only) are optional on dressed axles only
- All Hendrickson TRLAXLE<sup>®</sup> trailer axles are backed by an industry leading limited warranty\* and Hendrickson's superior customer and technical support
- AAXTREME COAT<sup>®</sup> premium brake shoe coating provides extreme protection in tough environments

See RTR READY-TO-ROLL Wheel-End Flyer - Literature No. L1200 See TIREMAAX PRO Brochure - Literature No. L1199 See AAXTREME COAT Flyer - Literature No. L1207 See MAXX22T Flyer - Literature No. L1239

\* For complete warranty terms, conditions and limitations, see the current version of Hendrickson's Comprehensive Warranty Statement L583 (available at www.hendrickson-intl.com). Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

### Call Hendrickson at 330.489.0045 or 866.RIDEAIR (743.3247) for additional information.

# HENDRICKSON

TRAILER COMMERCIAL VEHICLE SYSTEMS 2070 Industrial Place SE Canton, OH 44707-2641 USA 866.RIDEAIR (743.3247) 330.489.0045 • Fax 800.696.4416 Hendrickson Canada 250 Chrysler Drive, Unit #3 Brampton, ON Canada L65 6B6 800.668.5360 905.789.1030 • Fax 905.789.1033 Hendrickson Mexicana

Circuito El Marqués Sur #29 Parque Industrial El Marqués Pob. El Colorado, Municipio El Marqués, Querétaro, México C.P. 76246 +52 (442) 296.3600 • Fax +52 (442) 296.3601

L961 Rev H 01-20

© 2007 – 2020 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries, except for (1) Dura-Light Hub, which is owned by Walther Engineering & Manufacturing Company, Inc. and (2) MAXX22T, which is owned by WABCO. Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected. Printed in United States of America