

# SUSPENSION PSI TO LOAD CHART

**30K  
SUSPENSION  
INTRAAX®**

USING ONE OF THESE  
HENDRICKSON  
AIR SPRINGS

**AIR SPRING  
C-24445  
C-24446  
C-25319**

**Required**

**Load per axle**

**psi**

**(lbs)**

**(kg)**

|    |        |        |
|----|--------|--------|
| 89 | 30,000 | 13,608 |
| 83 | 28,000 | 12,701 |
| 76 | 26,000 | 11,793 |
| 70 | 24,000 | 10,886 |
| 64 | 22,000 | 9,979  |
| 58 | 20,000 | 9,072  |
| 52 | 18,000 | 8,165  |
| 45 | 16,000 | 7,257  |
| 39 | 14,000 | 6,350  |
| 33 | 12,000 | 5,443  |
| 27 | 10,000 | 4,536  |
| 20 | 8,000  | 3,629  |
| 14 | 6,000  | 2,722  |
| 8  | 4,000  | 1,814  |

**Trailer Commercial Vehicle Systems**  
2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045  
FAX 800.696.4416



**HENDRICKSON**

[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

**Hendrickson Canada**  
250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
905.789.1030  
FAX 905.789.1033