H TECHNICAL PROCEDURE TIREMAAX® TIRE INFLATION SYSTEM

SUBJECT: Rotary Union Spanner Wrench Use LIT NO: L941 DATE: November 2006

The rotary union spanner wrench serves two purposes. By fully inserting the prongs of the wrench into any two rotary union mounting holes, it offers a convenient way to hold the rotary union stationary while the threaded axle hose connection is tightened. And since the rotary union is manufactured in two halves, the prongs keep both halves of the rotary union from rotating while the axle hose connection is being made, thereby ensuring that the mounting holes in both halves of the rotary union stay aligned. Hendrickson recommends this tool when installing TIREMAAX in a trailer OE production environment. Refer to Hendrickson publication L844, *Installation Instructions For Rotary Union Replacement Kits*, available at www.hendrickson-intl.com, for complete rotary union replacement instructions.



H.HENDRICKSON

Trailer Suspension Systems 250 Chrysler Drive, Unit #3 Brampton, ON Canada L6S 6B6 905.789.1030 Fax 905.789.1033 Trailer Suspension Systems 2070 Industrial Place SE Canton, OH 44707-2641 USA 866.RIDEAIR (743.3247) 330.489.0045 Fax 800.696.4416 Trailer Suspension Systems Av. Industria Automortriz #200 Parque Industrial Stiva Aeropuerto Apodaca, N.L., México C.P. 66600 (52) 81 8288 1300 Fox (52) 81 8288 1301