

# **H** HT™ SERIES

## HT250US SPECIFICATIONS

LIT NO: L554

DATE: February 2020

REVISION: F

---





APPLICATIONS		
<b>CAPACITY<sup>1</sup></b>	25,000 lbs. (11 300 kg)	
<b>TRAILER TYPES</b>	<b>UNITED STATES AND CANADA</b> Drop Deck Van Auto Hauler Flat Lowboy / Drop Deck Dump Grain Livestock	<b>MEXICO, CENTRAL AND SOUTH AMERICA</b> None
<b>AXLE DATA</b>	5-inch diameter round, 5/8-inch min. wall <sup>2</sup> , 12.25-inch, 15-inch or 16.5-inch drum brakes	
<b>AXLE ARRANGEMENT</b>	Single, tandem (up to 122-inch max. axle spacing), tri or quad axle	
<b>FRAME TYPES</b>	Steel or aluminum	
<b>BASE MODEL DESCRIPTION:</b>	HT™ Series underslung suspension, standard travel, weld-on wingless frame brackets with QUIK-ALIGN® and forward mount standard shocks.	
<b>OTHER OPTIONS:</b>	Additional options include limited jounce and extended rebound travel, high control, bolt-on frame brackets, shock straps, remote shock mounting and extreme service/high damping shocks. Contact your Hendrickson representative to discuss these and other product options.	

## SPECIFICATIONS

SUSPENSION — HT250US (BASE MODELS <sup>3</sup> )			
RIDE HEIGHT (inches)	JOUNCE <sup>4,5</sup> (inches)	REBOUND <sup>4,5</sup> (inches)	WEIGHT <sup>6</sup> (pounds)
3.5	2.6	3.0	327
4.0	3.1	3.2	327
5.5	2.1	4.7	361
6.5	3.1	3.7	361
7.5	3.2	6.3	378
9.0	4.7	4.8	378
12.0	5.3	4.3	393
14.0	5.3	4.3	407

- Capacity refers to suspension only rating. Ratings for axle, brakes and wheel-end components differ depending upon options chosen.
- Refer to Hendrickson's literature L980 for Hendrickson axle capacity rating recommendations. A thicker axle wall should be considered in more demanding applications.
- Other models and options are available.
- Jounce rebound and weight figures shown are for models with standard weld-on hangers and standard shock absorbers. These values differ slightly for other models and options. Contact Hendrickson for more information.
- Limited axle travel configurations and extended rebound 6.5-inch ride height models are also available.
- Weight shown does not include the axle.

*Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.*

*All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.*

**Call Hendrickson at 330.489.0045 or 866.RIDEAIR (743.3247) for additional information.**



www.hendrickson-intl.com

**TRAILER COMMERCIAL VEHICLE SYSTEMS**  
2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045 • Fax 800.696.4416

**Hendrickson Canada**  
250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
800.668.5360  
905.789.1030 • Fax 905.789.1033

**Hendrickson Mexicana**  
Circuito El Marqués Sur #29  
Parque Industrial El Marqués  
Pob. El Colorado, Municipio El Marqués,  
Querétaro, México C.P. 76246  
+52 (442) 296.3600 • Fax +52 (442) 296.3601