

SUBJECT: HXS® Brake Packages LIT NO: B77 DATE: April 2000 REVISION: A

Hendrickson extended-service brakes (HXS[®] brakes) are available for INTRAAX[®] and VANTRAAX[®] suspensions in these sizes: $16^{1}/_{2}$ inches by 7 inches and $16^{1}/_{2}$ inches by $8^{5}/_{8}$ inches. HXS brake linings offer 27 percent more lining material than the standard brake lining on the 7-inch brakes and 58 percent more lining material on the $8^{5}/_{8}$ -inch brakes. The brake linings available are Abex 3030-197 for 20,000-pound applications and Abex 931-162 for applications requiring a higher brake rating of 23,000 pounds.

You can easily retrofit existing INTRAAX and VANTRAAX units with new HXS brake shoes, hardware, and s-cam. This retrofit is possible because the brake spider is in the same location for both the Hendrickson standard and HXS brake packages.

INTRAAX brake drum compatibility: in-line shoe design versus offset shoe design¹

The $16^{1}/_{2}$ -inch by 7-inch wide HXS brakes use the same drum as the standard brakes. However, the $16^{1}/_{2}$ -inch by $8^{5}/_{8}$ -inch, in-line shoe-design HXS brakes do not use the same drum as the older, non-HXS style $16^{1}/_{2}$ -inch by $8^{5}/_{8}$ -inch offset shoe design. The following drums are currently available and compatible with Hendrickson HXS $8^{5}/_{8}$ -inch wide brakes:

CAST		
	In-Line Shoe Design	Offset Shoe Design ¹
Dayton-Walther ²	85-123570-002	85-123406-002
Webb	66854B	66834
Gunite ²	3807	3779

FUSED-SHELL			
Dayton-Walther	53-123544-002		

¹The offset shoe is an early design and is no longer available. ²Currently, Hendrickson does not offer this drum.

For more information about the HXS brakes package, contact your Hendrickson Account Representative.



Trailer Suspension Systems 2070 Industrial Place SE Canton, OH 44707-2600 USA 330.456.7288 Fax 330.456.0105



Trailer Suspension Systems 250 Chrysler Drive, Unit #3 Brampton, ON L6S 6B6 Canada 905.789.1030 Fax 905.789.1033

> The Boler Company Copyright © 2000 All Rights Reserved