

ZMD[®]

EXCLUSIVE RIDE TECHNOLOGY



H HENDRICKSON
The World Rides On Us[®]

ZMD[®]

ZERO MAINTENANCE DAMPING[®]

Hendrickson provides the latest in ride technology with **ZMD[®] ZERO MAINTENANCE DAMPING[®] technology**. This patented system eliminates the need for an external damping component such as a shock absorber. Instead, the suspension damping function has been incorporated into the suspension air springs. ZMD's unique air spring design provides suspension damping and trailer isolation all in one package without adding additional components to the air spring.

What are customers saying about ZMD?

We decided to invest in ZMD ride technology to eliminate our shock maintenance expenses. An added bonus was the improved ride quality that our drivers experienced on top of that savings. Drivers in the fleet reported they felt a difference in the ride quality when the trailer was unloaded. Since our fleet runs loaded only 50% of the time, this will help us maintain our vessels as we tend to keep our trailers 20+ years.

Kyle Neumann
Maintenance Director

When specifying options for my trailers, I look for reduced maintenance and prolonged tire wear.

I noticed that the road hauling was excellent and the tire wear was also better than I had expected. All my expectations were met! Since then, I have purchased an additional two B-Trains with Hendrickson's ZMD technology and will continue to into the future.

Yvon Savoie
Owner
Transport Yvon Savoie

www.ridezmd.com

HOW ZMD[®] WORKS

As the axle moves up and down, pressurized air is exchanged between the flex member and the piston. By controlling this air flow, ZMD air springs provide continuous suspension damping for the entire life of the air spring.



FEEL THE DIFFERENCE

Hendrickson's ZMD technology does a superior job of isolating the trailer from road inputs whether fully loaded or dead heading. ZMD helps to diminish the fore and aft forces transmitted to the trailer from the suspension by damping as the suspension travels up and down providing a more comfortable ride for the driver.

More Comfortable

Less Wear

Greater Protection



**Watch ZMD
in action**

ZMD® Features and Benefits

Patented Air Spring

- Superior ride quality and driver comfort
- Reduced overall suspension maintenance
- Uniform damping levels over the life of the air spring
- Enhanced cargo protection
- Increased trailer component life
- No moving parts
- No hydraulic fluid

Robust Down Stop

- Reduced labor and costs
- Less maintenance
- Reduced risk of roadside inspections and CSA violations



Specifications

	MODEL	RIDE HEIGHTS (in)	NOTES
ULTRAA-K®	UTKNT 40K	16	Standard
VANTRAAX®	HKANT 40K	16	Optional; Requires QUIK-DRAW®
VANTRAAX	HKANT 46K	15, 16, 17	Optional; Requires QUIK-DRAW
VANTRAAX	HKAT 50K	16, 16.5, 17, 18	Optional; Requires QUIK-DRAW
VANTRAAX	HKANT 69K23	16, 17	Optional; Requires QUIK-DRAW
VANTRAAX	HKAT 75K25	16, 16.5, 17, 18	Optional; Requires QUIK-DRAW
VANTRAAX	HKAT 69K25	16, 16.5, 17, 18	Optional; Requires QUIK-DRAW
INTRAAX®	AANT 23K	14, 15, 16, 17	Optional; Standard travel only
INTRAAX	AAT 23K*	14, 15, 16, 17	Optional; Standard travel and limited rebound*
INTRAAX	AAT 25K*	14, 15, 16, 17, 18, 19	Optional; Standard travel and limited rebound*
INTRAAX® SP	AAZNT 23K	13.5, 14, 15, 16, 17	Optional
INTRAAX SP	AAZNT 46K	13.5, 14, 15, 16, 17	Optional
INTRAAX SP	AAZNT 69K23	13.5, 14, 15, 16, 17	Optional

*RCA Raised-Center Axle is available on AAT 23K / 25K models equipped with ZMD for both standard and limited rebound travel. Only 14" or 16" ride heights are available with limited rebound travel when spec'ing RCA.

Warranty

ITEM	PARTS	LABOR
ZMD® "Shockless" Ride Technology		
ZMD Air Springs	3 years	3 years
ZMD Down Stops	3 years	3 years
Traditional Air Springs & Shock Absorbers		
Air Springs	2 years	1 year
Shock Absorbers	2 years	2 years

See L583 Comprehensive Warranty Statement or contact Hendrickson for complete warranty terms, conditions and limitations.

FREQUENTLY ASKED QUESTIONS



Scan for more info

1. Why is ZMD® limited to specific ride heights on ULTRAA-K®, VANTRAAX®, INTRAAX® SP and select top-mount INTRAAX® models?

ZMD is currently limited because this patented air spring and down stop has been rigorously tested for these specific applications.

2. How are ZMD air springs installed?

ZMD air spring installation procedures and mounting hardware are identical to standard air spring and shock installation procedures. To install ZMD air springs as a retrofit, simply remove the existing shocks and air springs and replace with ZMD air springs and down stops. The select INTRAAX AANT 23K models that are available with ZMD require an additional bolt to be added to the shock clevis on winged hangers only. Follow all applicable Hendrickson installation, service, maintenance and repair procedure publications.

3. Can standard air springs be mixed with ZMD air springs?

NO. Mixing ZMD air springs with standard air springs is not recommended. While the load curves for each product are somewhat similar, they provide different damping performance to the suspension system. Mixing ZMD and standard air springs on the same suspension can adversely affect the operation and life of other integral suspension components.

4. Can ZMD air springs equipped on VANTRAAX, INTRAAX and INTRAAX SP suspensions be interchanged?

NO. Both ZMD and standard air springs are specially designed to meet the needs and geometry of the specific application. It is important to use only the exact air springs specified by Hendrickson for each model to ensure maximum operation performance and life of components.

5. How can customers tell the difference between a ZMD air spring and a standard air spring?

The customer must visually inspect the air spring to verify the type of air spring.

Identifiers include:

- ZMD embossed on the bellows
- Part number
- Down stop instead of shocks

Similar to today's standard air springs, the Hendrickson part number will be located on the ZMD air spring bellows.

6. Can ZMD be retrofitted on existing trailers in service?

YES. ZMD air springs and down stops can be retrofitted on compatible VANTRAAX, INTRAAX, and INTRAAX SP models with certain specifications. For more questions on ZMD retrofits, contact your Hendrickson customer service representative or Hendrickson at 1-866-RIDEAIR (743-3247).

These products are covered by at least one or more U.S. and / or foreign patents and / or pending U.S. and / or foreign patent applications. See Hendrickson for details.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.

Contact Hendrickson for additional details regarding specifications, applications, capacities, operation, service and maintenance instructions.

Call Hendrickson at 330.489.0045 or 866.RIDEAIR (743.3247) for additional information.



www.hendrickson-intl.com



TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
Fax 800.696.4416

HENDRICKSON CANADA ULC

2825 Argentina Road, Unit #1 - 4
Mississauga, ON Canada L5N 8G6
800.668.5360
905.789.1030 • Fax 905.812.9423

HENDRICKSON MEXICANA

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México CP 76246
+52 442.296.3600 • Fax +52 442.296.3601

L1314 Rev C 02-25

© 2015 - 2025 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries. Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected. Printed in United States of America