

Hendrickson Equalizing Beam Center Bushings

Each Hendrickson center bushing is engineered for specific types of Hendrickson walking beam suspension capacities, applications, and configurations to maximize system performance. To help ensure high end user satisfaction and peak system performance Hendrickson supplies the same genuine components for service requirements as were installed in the original suspensions.

Rubber Center Bushings — Proprietary rubber compound provides maximum bushing life while maintaining system performance attributes.



High Confinement Center Bushings

- Standard on all Hendrickson walking beam suspensions rated up to a 40,000 pound capacity
- Can be specified up to a 46,000 pound capacity rating, when used in conjunction with transverse rods
- Maintains a high resistance to bushing walkout over a longer period of time due to the confinement of the rubber



Fully Bonded Center Bushings

- Designed for high-capacity Hendrickson walking beam suspensions rated at 52,000 pound capacity
- Low maintenance, helps maintain low tire wear
- Provides the extra strength and durability necessary to routinely handle heavy loads
- The bonded rubber to metal resists friction, therefore improving bushing life

NOTE: These rubber bushings are also available with a loose plug for ease of cross tube installation

Bronze Center Bushings



- Designed for severe applications that encounter extremely tight turns under heavy loads that are not equipped with transverse torque rods
- Standard on Hendrickson walking beam suspensions rated at 46,000 and 52,000 pound capacities
- Bronze bushing grease channels are precisely cut and located to ensure proper grease flow and long bushing life

To learn more about Hendrickson
Genuine Parts call 1.866.755.5968
or visit www.hendricksonparts.com

GENUINE PARTS Center Bushing Parts and Kits

STANDARD DUTY RUBBER CENTER BUSHINGS

Hendrickson rubber bushings require no lubrication maintenance and provide solid performance in a variety of applications.



Part Number	Capacity
06664-000L	34K
22279-000L*	34K
05919-000L	38K
22282-000L*	38K



Part Number	Capacity
49400-000L	40K
49600-000L*	40K



Part Number	Capacity
47420-000	E4 34K-40K HFS 36K-40K

HIGH CAPACITY RUBBER CENTER BUSHINGS

These bushings are designed specifically to stand up to higher capacities and severe service applications and require torque rods.



Part Number	Capacity
29483-005L	46K-52K
34013-097L*	46K-52K
10366-000L	65K

* Loose Plug

BRONZE CENTER BUSHING SERVICE KITS

Hendrickson bronze bushings are not to be used with transverse torque rods.



Kit Number	Capacity
30437-000L	40K-46K
34013-054L	40K-52K
30240-002	52K

TECHNICAL NOTES

- The decision to use rubber or bronze center bushings is dependent on a variety of factors dictated by the operating conditions, geographic location, and configuration of the vehicle. Refer to Hendrickson's Equalizing Beam and Components Selection Guide Literature No. 45745-147 for more details, available online at www.hendrickson-intl.com.
- To convert center bushings from bronze to rubber, contact Hendrickson Truck Parts at 1-866-755-5968 or e-mail: truckparts@hendrickson-intl.com.



Call your truck dealer or Hendrickson at **1.866.755.5968** (toll-free) or **1.630.910.2800** for additional information.



www.hendrickson-intl.com

TRUCK COMMERCIAL VEHICLE SYSTEMS

800 South Frontage Road
Woodridge, IL 60517-4904 USA
1.866.755.5968 (Toll-free U.S. and Canada)
1.630.910.2800 (Outside U.S. and Canada)
Fax 1.630.910.2899