HHCA HENDRICKSON CHASSIS AXLE

- Proven performance
- Industry-standard chassis axle
- Less downtime



Worldwide Product Support

As a leading supplier to the global commercial vehicle market, Hendrickson boasts a wide breadth of product and application knowledge. Our sales and service teams are available to provide support – from applications advice to onsite training.

Low-Maintenance

Hendrickson's product testing and specifications provide durable, low-maintenance parts. The HCA® system features a robust design that has durability in mind. From heat treated spindles to hardened cam heads, journals and splines, the HCA is ready for kilometer after kilometer.

Outstanding Warranty Coverage

Hendrickson's industry-leading warranty guarantees outstanding coverage and support from a recognised name in the commercial vehicle industry and the convenience of a single source supplier.

To learn more about HCA Hendrickson Chassis Axle, call Hendrickson or visit our global websites for additional information.




HCA® HENDRICKSON CHASSIS AXLE™ Features and Benefits

Brakes and RTR® Wheel-Ends

- 9t capacity (20,000 lbs.)
- 420 × 180mm (16.5 × 7 in.) standard service – fast change shoes using Hendrickson proprietary 9t (20,000 lbs.) lining
- E-Coated brake shoes for protection against rust jacking
- Forged S-cams with hardened head, journals and splines
- Lightweight outboard mounted cast iron brake drums
- Cam shafts removable without removing the hub on hub piloted
- ABS ready
- Hub piloted hubs
- 335mm and 11.25 in. hub bolt circles
- Premium Federal Mogul seal
- Hendrickson's patented axle filter and axle venting system
- Patented PRECISION240® or PRECISION320® systems allow for ultra-precise bearing adjustment
 - HLS® Hendrickson Long-Life System™ standard with a 6-year parts and labour warranty*



- Heat treated 127mm (5 in.) diameter axle
- Heat treated, hot-formed HN and HP spindles
- 9t capacity (20,000 lbs.)
- 1816mm to 1968mm (71.5 to 77.5 in.) standard axle tracks. Other axle tracks available.
- Axle bar warranted for 7-year parts / 7-year labour, extended warranties available*
- For complete warranty terms, conditions and limitations, see the current version of Hendrickson's HCA Hendrickson Chassis Axle Warranty L1026 (available at www.hendrickson-intl.com) or call Hendrickson.



- TIREMAAX® PRO and CP tyre inflation systems help maximise tyre life and maintain peak fuel mileage
- 420 \times 180mm (16.5 \times 7 in.) HXS® and 420 \times 220mm (16.5 × 8.625 in.) HXS Hendrickson Extended Service™ brakes extend intervals between brake service
- 140 or 152mm (5.5 or 6 in.) auto slack adjusters and manual slack adjusters available
- Brake chambers in various configurations
- ABS sensor installation available
- Dura-Light Hub® and aluminum hubs available
- Dust shields available
- Spring seat installation available
- 12 to 19mm (0.5 to 0.75 in.) axle wall thickness available

Specifications

Model	Suspension Capacity (metric tonnes)	Axle Diameter (mm)	Tracks (mm)	Base Model Weight (kg)
НСА	9t (20,000 lbs.)	127mm (5 in.)	1816 to 1968mm (71.5 to 77.5 in.)	279 to 284kg (615 to 626 lbs.)

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. For additional details regarding specifications, applications, capacities and service maintenance instructions, contact Hendrickson. Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

Call Hendrickson or visit our global websites for additional information.

500 Park Boulevard, Suite 450 Itasca, IL 60143-1285 USA +1.630.874.9700

Hendrickson Commercial Vehicle **Systems Europe**

IAA045 Rev A 07-18

Hendrickson Austria GmbH Gussstahlwerkstraße 21 A-8750 Judenburg, Austria +43 3572 44011 400

eu.hendrickson-intl.com

Hendrickson Truck Commercial Vehicle Systems 800 South Frontage Road Woodridge, IL 60517-4904 USA

+1.855.743.3733 +1.630.910.2800

www.hendrickson-intl.com

Hendrickson Trailer Commercial **Vehicle Systems** 2070 Industrial Place SE

Canton, OH 44707-2641 USA +1.866.743.3247

+1.330.489.0045 www.hendrickson-intl.com

Hendrickson Commercial Vehicle Systems Australia 32-44 Letcon Drive

Dandenong South, Victoria, 3175 Australia +61 3 8792 3600

aus hendrickson-intl.com

Hendrickson Commercial Vehicle **Systems China**

No. 1668 North Section of Chunbo Road East New Dist of Jinan High-Tech Industrial Development Zone, Jinan City, Shandong Province, China, 250104 +86 531 8880 9055

china.hendrickson-intl.com

Hendrickson Commercial Vehicle Systems India

Plot No. 4 & 5, Gat. No. 679/2 Behind Hotel Gandharva Alandi Kuruli Road, Kuruli (Chakan) Taluka Khed, Pune 410501, India +91 2135 662600

india.hendrickson-intl.com

Hendrickson Commercial Vehicle Systems UK

1-9 Booth Drive Park Farm Industrial Estate Wellingborough, NN8 6GR, England +44(0) 1604 493161

uk.hendrickson-intl.com

"HENDRICKSON," the "H" logo and other Hendrickson marks designated with the "®" symbol are registered trademarks of Hendrickson USA, LL.C. in the United States and certain other countries.

Dura-Light Hub is a U.S. registered trademark owned by Walther Engineering & Manufacturing Comany, Inc.

Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

© 2018 Hendrickson USA, LL.C. All Rights Reserved